

KNX DALI-Gateway Basic REG-K/2/16/64

MTN6725-0004

Main

Range of product	SpaceLogic KNX	
Product or component type	DALI gateway	
Number of output channels	2	
Bus type	KNX	
Function available	Updateable software	
Colour tint	White	

Complementary

Mounting support	DIN rail
total number of 18 mm modules	4
[Ue] rated operational voltage	100240 V
Network frequency	50/60 Hz
Communication port protocol	DALI
Local signalling	LED
Main colour tint	White
Market segment	Buildings Commercial Critical buildings Lodging/hotel School Office Small commercial

Environment

IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.200 cm
Package 1 Width	13.300 cm
Package 1 Length	15.900 cm
Package 1 Weight	228.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	28

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	6.984 kg

Contractual warranty

Warranty (in months)

18



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	177
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	No	
Packaging without single use plastic	Yes	
EU RoHS Directive	Compliant	
SCIP Number	6756a690-405c-48e4-87ab-bcde04eda8b8	
REACh Regulation	REACh Declaration	

Use Again

○ Repack and remanufacture		
End of life manual availability	End of Life Information	
Take-back	No	
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	