

Product datasheet

Specifications



SpaceLogic KNX Switch/Blind Extension 8ch 10AX/16AC1

MTN6805-0008

Main

Range	SpaceLogic KNX
Product or component type	Blind switch actuator
Bus type	KNX
Operating mode	KNX bus system
rated input	ON/OFF status:

Complementary

Mounting support	DIN rail
[Ue] rated operational voltage	250 V AC 50/60 Hz
[In] rated current	16 A 10 A
Number of outputs	8 4
Colour tint	White

Environment

IP degree of protection	IP20
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.700 cm
Package 1 Width	12.400 cm
Package 1 Length	15.700 cm
Package 1 Weight	369.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	24
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm
Package 2 Length	60.000 cm
Package 2 Weight	9.596 kg

Contractual warranty



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint 13

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard No

Packaging without single use plastic No

[EU RoHS Directive](#) Compliant with Exemptions

SCIP Number 742aa773-90f8-499c-9f60-f02cbbc0de1e

REACH Regulation [REACH Declaration](#)

Halogen-free status Halogen free product

PVC free Yes

Use Longer

Lifetime extension

Repair No

Use Again

Repack and remanufacture

End of life manual availability [End of Life Information](#)

Take-back No

WEEE Label  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative







